

REVISIONS						
ZONE	REV	ECN	DESCRIPTION	DATE	DR	CK
	A		INITIAL RELEASE	2021SEP24	JK	GM
	B	1511223	FORMER MODEL NUMBERS ADDED	2024APR15	K.SHRINIDHI	M.SMITH

3200 BOTTOM DRIVE "DOUBLE ENVELOPE" LIP SEAL UNIT SHOWN. TOP DRIVE SIMILAR.
SEE TABLE FOR MODELS WITH DIFFERING LENGTHS

SHAFT "H"
WITH KEY "J"

3/4" NPT INSTRUMENTATION
CONN. (2) INLET PORT
(1) OUTLET PORT

OIL FILL PLUG
ONE EACH END

1/2 NPT
TEMP SWITCH
OUTLET PORT

ALTERNATE DRIVE SHAFT
LOCATION

OPTIONAL SPM MOUNT
(3) EACH END PLATE

"G" FLANGE
150# ANSI PATTERN

OIL LEVEL GAUGE
ONE EACH END

OIL DRAIN PLUG
ONE EACH END

DRAIN PLUG

Ø 13/16
4 HOLES

-	-	OVERALL LENGTH	SHAFT-PORT LENGTH	PORT-REAR LENGTH	FOOTPRINT LENGTH	PORT WIDTH	PORT STD / METRIC (mm)	SHAFT Ø STD / METRIC (mm)	KEY SIZE STD / METRIC (mm)	SHAFT LENGTH STD / METRIC (mm)	APPROX WEIGHT (lbs)
MODEL	FORMER MODEL	DIM "A"	DIM "B"	DIM "C"	DIM "D"	DIM "E"	DIM "G"	DIM "H"	DIM "J"	DIM "K"	-
3200	9016	49.67	29.08	20.59	27.56	30.70	12 / 300	3.12 / 48	.75 SQ x 5.50 / 22 x 14 x 145	6.20 / 157	1710
4200	9020	54.92	31.54	23.05	32.48	30.70	12 / 300	3.12 / 48	.75 SQ x 5.50 / 22 x 14 x 145	6.20 / 157	1950
5400	9027	61.48	34.98	26.49	39.37	30.70	14 / 350	3.12 / 48	.75 SQ x 5.50 / 22 x 14 x 145	6.20 / 157	2185
7300	9036	70.14	39.31	30.82	48.03	30.70	16 / 400	3.12 / 48	.75 SQ x 5.50 / 22 x 14 x 145	6.20 / 157	2600

UNLESS OTHERWISE SPECIFIED
US CUSTOMARY IN

XX-0.25

BREAK ALL SHARP EDGES, CORNERS,
DEBURR AND CLEAN

INTERPRET PER ASME Y14.5-2009
THIRD ANGLE PROJECTION



NOTICE OF CONFIDENTIAL INFORMATION
INFORMATION CONTAINED HEREIN IS
CONFIDENTIAL AND IS THE PROPERTY OF M-D
PNEUMATICS KINNEY. THE INFORMATION
SHALL NOT BE USED OR DISCLOSED BY THE
RECIPIENT FOR ANY OTHER PURPOSE
WHATSOEVER.

APPROVALS

DRAWN JK

CHECKED KM

DATE

09/23/2021

09/24/2021

M-D Pneumatics® KINNEY®

TITLE

3200-7300 BOOSTER OUTLINE
HORIZONTAL SPLASH

SIZE DWG NO.

D 3200-7300 HORZ SPLASH

SCALE 1:8

WEIGHT

SHEET 1 OF 1

REV

B